

# Technical Data

## AirTalk XSN - USB



Neckband headset for professional use in the field of ATC

- lightweight monaural neck holder headset
- turnable and hinged earpiece
- pressure free, most durable and flexible
- replaceable leatherette ear cushion
- Acoustic-Shock-Protection (ASP)

### Technical data

#### Send button

Life cycle: min. 10.000.000 cycles  
 MTBF: approx. 100.000 h  
 Protection class: IP43  
 Operation voltage: +/- 12 V  
 Power input: 15 mA  
 Distortion: 0,2 %  
 Housing: PC/ABS T45, black  
 Amplification: approx. 28 dB

#### Speaker

Pattern: dynamic  
 Impedance: 600 Ohm at 1 mW / 1 kHz  
 Sound pressure level: max. 117 dB  
 Frequency range: 100 Hz – 8 kHz  
**Microphone**  
 Pattern: electret  
 Directional: Noise Cancelling (NC)  
 Impedance: 1100 Ohm

Sensitivity: -41 dB V / Pa, 1 kHz  
 Frequency range: 100 Hz – 10 kHz

#### Additional Data

Weight: 106 g (incl. PTT button)  
 Temperature range: -20°C to +70°C

#### Additional data

System requirement: USB 2.0, or later, Windows XP,7,8.1,10, Linux Kernel 2.6, or later

[www.intradex.com](http://www.intradex.com)