

Technical Data

AirTalk NBS - USB



Light Headset for professional use in the field of ATC with USB plug

- extreme lightweight monaural neck holder headset
- for professional use in the field of ATC
- Acoustic-Shock-Protection (ASP)
- Noise-Cancelling electret microphone
- convenient, break proof and flexible neckband
- replaceable ear cushions

Technical data

Send button

Life cycle: min. 10.000.000 cycles
 MTBF: approx. 100.000 h
 Protection class: IP43
 Operation voltage: +/- 12 V
 Power input: 15 mA
 Distortion: 0,2 %
 Housing: PC/ABS T45, black
 Amplification: approx. 28 dB

Speaker

Pattern: magnetic
 Impedance: 250 Ohm at 1 mW / 1 kHz
 Sound pressure level: max. 117 dB
 Frequency range: 100 Hz – 4 kHz
Microphone
 Pattern: electret
 Directional: omni-directional
 Impedance: 2200 Ohm

Sensitivity: -40 dB V / Pa, 1 kHz
 Frequency range: 100 Hz – 10 kHz

Additional Data

Temperature range: -20°C to +70°C
 Weight: 118 g (incl. PTT button)

Additional data

System requirement: USB 2.0, or later, Windows XP,7,8.1,10, Linux Kernel 2.6, or later

www.imtradex.com