

Technical Data

AirTalk XS - USB



Light monaural headset with electret microphone for use in ATC area

- Protect the ear from high volumes due to the Acoustic-Shock-Protection
- Raised edge on the top side of the microphone for optimal alignment
- Ear cushions of Coolmax® ensure high breathability
- High wearing comfort thanks to optional Spacer Distance-Clip
- optimum noise compensation

Technical data

Send button

Life cycle: min. 10.000.000 cycles
 MTBF: approx. 100.000 h
 Protection class: IP43
 Operation voltage: +/- 12 V
 Power input: 15 mA
 Distortion: 0,2 %
 Housing: PC/ABS T45, black
 Amplification: approx. 28 dB

Speaker

Pattern: dynamic
 Impedance: 600 Ohm at 1 mW / 1 kHz
 Sound pressure level: 90 dB 1mW/1 kHz
 Frequency range: 200 Hz – 10 kHz
Microphone
 Pattern: electret
 Directional: omni-directional
 Impedance: 2200 Ohm

Sensitivity: -40 dB V / Pa, 1 kHz
 Frequency range: 100 Hz – 10 kHz

Additional Data

Temperature range: -20°C to +70°C
 Weight: 195 g (incl. PTT button)

Additional data

System requirement: USB 2.0, or later, Windows XP,7,8.1,10, Linux Kernel 2.6, or later

www.intradex.com